

3.2m C/Ku-Band Rx Only Antenna



Features:

- Aluminum reflector with high precision
- Fashionable design, easy installation and adjustment
- Factory feed system and king post pedestal assembled to reduce installation time
- No Field alignment required
- Excellent in stability

3.2m C/Ku-Band Rx Only Antenna Specifications

◆ R.F SPECIFICATIONS	C-Band	Ku-Band
	RECEIVE	RECEIVE
1. Frequency (GHz)	3.625-4.2 3.4-4.2 ★ 40.55 at 3.8GHz 1.3:1 1.542°	12.25-12.75 10.95-12.75 ★ 50.57 at 12.5GHz 1.3:1 0.487°
5. Antenna Noise Temperature (K)	1/2Port Feed	1/2Port Feed
10° Elevation	36K	42K
20° Elevation	31K	37K
40° Elevation	27K	33K
6. Typical G/T at 20°EL	22.7dB/K(3.8GHz, 30K LNA)	30.28dB/K(12.5GHz, 70K LNA)
7. Feed Interface	CPR-229	WR-75
8. Feed Insertion Loss	0.15dB	0.2dB
9. Axial Ratio (dB)	0.75dB	1dB
10. Cross Pol Isolation		
On Axis	≥30dB	≥30dB
11. Sidelobes	CCIR.580-6	CCIR.580-6
◆ MECHANICAL SPECIFICATION		◆ ENVIRONMENTAL SPECIFICATION
1. Antenna Type	Prime-focus	1. Wind Loading,Operational (Maintain Precision)
2. Drive Type	Manual	45mph(72km/h)
3. AZ Travel	0 to 360°	60mph(97km/h)
4. EL Travel	5° to 90°	125mph(200km/h)
5. POL Travel	±90°	-40°C to 60°C
6. Reflector Material	Precision formed aluminum	100mm/h
7. Reflector Segments	12	0 to 100%
8. Mount Type	King post pedestal	6. Relative Humidity
		7. Solar Radiation
		8. Ice
		25mm on all surface or 13mm on all surface with
		9. Shock and Vibration
		10. Seismic (Survival)