



MTM5000 Series TETRA two-way mobile radio

The MTM5000 Series TETRA mobile radios are sleek and durable and packed with features that have become essential for safe and effective operations. These include End-to-End Encryption and features that enable ease of operation in the most demanding situations such as high audio quality, high receiver sensitivity, an intuitive keypad, and a high-definition colour display.

The MTM5000 series mobile radios support a wide range of applications and installation options including: fixed control room, vehicle, motorcycle and custom installation.

MTM5000 Series benefits

- Extended Operational Range
- Superior Audio Performance
- Low User Migration Costs
- Enhanced End-to-End Encryption Options
- Location Services
- Advanced Terminal Management
- Flexible Installation Options
- Rugged Design with Exceptional Reliability



MTM5000 Series specifications



	MTM5400	MTM5500
MODELS - COMPLIANT WITH DIN 75490 (ISO 7736)		
Dash	Compact radio for fast vehicle installation	N.A.
Desk	Compact radio, for use in the office. Optional range of accessories such as desk tray with integrated loudspeaker	N.A.
Multiple Remote Control Head	N.A.	Radio with multiple remote mount control head capability
Multiple Transceiver or Control Head	N.A.	Range of installation options enable use in cars, vans and other vehicles
Motorcycle	Radio with multiple remote mount control head capability Environmentally enhanced radio meeting IP67 specification. Suitable for demanding environments such as motorcycle, fire appliance and marine installations	N.A.
Expansion head "Databox"	Radio without a control head, for data applications, or customised application development	

GENERAL

		MTM5400	Dimensions H x W x D (mm)	Weight Typical (g)	MTM5500	Dimensions H x W x D (mm)	Weight Typical (g)
Dash / Desk Mount	Transceiver & Control Headhead		60 x 188 x 202	1,500		N.A.	
	Dash / Desk Control Head		60 x 188 x 31	230		N.A.	
Remote Mount	Transceiver & Expansion Head		45 x 170 x 185	1117		45 x 170 x 196	1330
	Remote Control Head		60 x 188 x 39	300		60 x 188 x 39	330
	IP67 Control Head		60 x 188 x 39	320		N.A.	
	Telephone Style Control Head		N.A.			220 x 65 x 75	450 (excluding cable)
Databox	Transceiver & Expansion Head		45 x 170 x 194	1201		45 x 170 x 196	1330

USER INTERFACE & DISPLAY

Display	Diagonal dimension	2.8"	
	Type	VGA - 640x480 pixels, 65,000 colours	
	Backlight	Variable backlight, User configurable	
	Font sizes	Standard & Zoom mode (90 pixels, 4.5mm high) characters	
TSCH		N.A.	Available as option
Buttons & Keypad	Numeric	Integral backlit numeric keypad of 12 keys, with keypad lock option	
	International keypad versions ¹	Roman, Arabic, Cyrillic, Korean, Chinese, Taiwanese characters	
	Programmable function keys	3 programmable function keys (plus 10 programmable numeric keys)	
	Navigation	4-way navigation key, menu and soft keys	
Rotary	Emergency Shortcuts	Emergency button with backlight	
	Dual Function	User configurable shortcuts to menus and common features using "One-Touch-Button" feature	
Indication	LED	Talkgroup and volume change with lock option	
	Tones	Tri-colour LED Configurable notification tones	
User Interface Languages	Standard Options	Arabic, Chinese Simplified, Chinese Traditional, Croatian, Danish, Dutch, English, French, German, Greek, Hebrew, Hungarian, Italian, Korean, Lithuanian, Macedonian, Mongolian, Norwegian, Portuguese, Russian, Spanish, Swedish	
	User defined	User programmable, using ISO 8859-1 character	
Menu		Tailored to user needs Menu Shortcuts Menu Configuration	
Contacts Management		Cellular Type	
Contact List		Up to 1,000 contacts	
Multiple Dialling Methods		Up to 6 numbers per contact, Max 2,000 numbers	
Fast/Flexible Call Response		User selects how to dial	
Multiple Ring Tones		Private Call Response to a Group Call via One Touch Button	
Message Manager		Configurable with CPS	
Text message list		Cellular Type	
Intelligent Keypad Text Input		20	
Status list		All Control Heads	
Country/Network Code List		400	
Scan lists		100	
Discrete Mode		40 lists of 20 groups	
Screen Saver		All Control Heads	
Universal Time Display		gif image & text (any user's selection)	
Keypad Lock		All Control Heads	
Talkgroup Folders		All Control Heads	
Favourite Folders		Dual layer folder structure (folder/subfolder) 256 folders Up to 3 (to store any favourite talkgroup)	

¹ For availability of other language keypads please contact your local Motorola Solutions representative

MTM5000 Series specifications

		MTM5400	MTM5500
ELECTRICAL SPECIFICATIONS			
Voltage Range		10.8 to 15.6 V DC	
Current Consumption (A, typ.)	Idle / Rx / Tx @ 10W	0.5 / 1.0 / 1.2 (TX 3.4A Peak)	
	Idle / Rx / Tx @ 3W	0.5 / 1.0 / .9 (TX 2.2A Peak)	
	Tx - Multi Slot PD (4 slots) @ 5.6W	2.7	
	Using USB host	Adds 0.5A	
RF SPECIFICATIONS			
Frequency Bands (MHz)		350 - 390, 380 - 430, 410 - 470, 806 - 870	
Transmitter RF Power	TETRA Release 1	10W (Class 2) and 3W (Class 3)	
RF Power Control	6 Power Step Levels (steps of 5 dBm)	Starting at 15 dBm; finishing at 40 dBm	
Receiver Class		A & B	
Receiver Static Sensitivity (dBm)		-114 minimum, -116 typical (ETSI 300-392-2)	
Receiver Dynamic Sensitivity (dBm)		-105 minimum, -107 typical (ETSI 300-392-2)	
GNSS SPECIFICATIONS			
Simultaneous Satellite Systems		GPS plus one other GNSS, eg GLONASS, BeiDou	
Mode of Operation		Concurrent tracking, SBAS capable, 72 channel	
GNSS Antenna		Supports active antenna (5V, 25mA supply)	
Acquisition Sensitivity		-145 dBm (guaranteed); -146 dBm (typical)	
Tracking Sensitivity		-162 dBm (guaranteed); -163 dBm (typical)	
Horizontal Accuracy, 2D		5m (95% probable) @ -130dBm	
Location Protocols		ETSI Location Information Protocol (LIP) Motorola LRRP	
ENVIRONMENTAL SPECIFICATIONS			
Operating Temperature (°C)		-30 to +60	
Storage Temperature (°C)		-40 to +85	
Not in use - Storage	ETSI 300 019-1-1 CLASS 1.3	Non-Weather Protected Storage Locations	
Not in use - Transportation	ETSI 300 019-1-2 CLASS 2.3	Public Transportation	
Stationary use - Weather Protected Locations	ETSI 300 019-1-3 CLASS 3.2	Partly Temperature Controlled Locations	
Mobile use - Ground Vehicle Installation	ETSI 300 019-1-5 CLASS 5.2	Climatic Tests	
Mobile use - Ground Vehicle Installation	ETSI 300 019-1-5 CLASS 5M3	Mechanical Tests	
Rail Certification Environmental	EN50155:2007 and IEC60571 ED.3.0	Environmental	
MIL STD	810 C/D/E/F/G Specifications	All 11 categories met (or exceeded)	
Dust and Water Ingress Protection	IP54 (dust cat. 2)	Dash/Desk/Remote models	
	IP67	Motorcycle model (only control head is IP67; transceiver is IP54)	MTM5500 TSCH IP55
VOICE SERVICES			
Talkgroups		10,000 TMO, 2,000 DMO	
Phone book entries		1,000 persons. Up to 6 numbers per entry (mobile, office etc). Max 2,000 entries	
Scan lists		40 lists of 20 talkgroups	
Trunked Mode (TMO) Services	Group call	Late Entry, TMO/DMO Mapping	
	Private call	Half / Full Duplex	
	Telephony (PABX, PSTN, MS-ISDN)	Full Duplex	
	DGNA	Up to 10,000 groups	
Direct Mode (DMO) Services	Scanning	Attachment signalling, supports SWMI initiated attachment/detachment	
		Group call Private call	
Emergency (tailored by users)	Tactical	Emergency Group Call to ATTACHED talkgroup	
	Non-Tactical	Emergency Group Call to DEDICATED talkgroup	
	Individual	Emergency Call to PREDEFINED party (half/full duplex)	
	Smart emergency	TMO to DMO and DMO to TMO automatic switching options	
	Hot Mic	Configurable timers for automatic open mic (talk without PTT)	
	Location	Location (GPS) sent with emergency	
	Target Address	Sent to individual or group address (selected or dedicated)	
Alarm (status message)	Emergency Status (or other pre-defined status)		
DATA SERVICES			
Status	Alias messages Options	400 Entries Can be sent via One-Touch or via menu	
Short Data Service (SDS)	Inbox/Outbox	Up to 200 Entries (short messages) At least 20 Entries for Outbox (long messages) ² At least 10 Entries for Inbox (long messages) ²	
	Predictive Text	Cellular style iTAP predictive text entry	
	Target Address	Sent to individual or group address (selected or dedicated)	
Packet Data (PD)	Voice Call Interaction	SDS messages can be sent and received during a voice call	
	Multi-slot PD	Data transmission with up to 4 slots supporting up to 28.8 kbit/s gross	
WAP	Integrated WAP browser	Integrated Openwave browser	
	(including WAP-PUSH)	WAP 1.2.x and WAP 2.0 compatibility for UDP/IP Stack	
Peripheral Equipment Interface (PEI)		AT Commands - Full Set ETSI Mandatory Compliant	
	Interface Protocol	AT Multiplexer - 4 Virtual Physical Port (simultaneous PD, SDS, AT commands and Air Tracer SESSIONS) TNP1; enables simultaneous PD and SDS sessions	
Terminal Management		Programmable via Motorola Integrated Terminal Management (iTM) solution	

² Long messages of up to 1,000 characters

MTM5000 Series specifications

		MTM5400	MTM5500
GATEWAY SERVICES			
DMO/TMO Gateway	Group voice calls from DMO to TMO		
	Group voice calls from TMO to DMO		
	Emergency group call from DMO to TMO		
	Emergency group call from TMO to DMO		
	Call Pre-emption (in either direction)		
	SDS messaging through the gateway from DMO to TMO or TMO to DMO		
	Configurable routing of SDS messages to console or PEI ³		
Point to point calls and SDS messages whilst operating as a Gateway			
REPEATER SERVICES			
DMO Repeater	Repeats DMO voice calls on selected talkgroup		
	Repeats SDS and Status messaging on selected talkgroup		
	ETSI type 1A DMO Repeater for channel efficient operation		
	Transmission of Repeater Presence Signal		
	Priority Call		
	Emergency Call (Pre-emptive Priority Call)		
	E2EE Encrypted DMO traffic		
	Monitoring of and participation in calls whilst in Repeater mode		
Configurable Repeater Power Levels			
INTERFACES			
RS232	Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT		
USB	USB 2.0 support for PEI (Two Virtual Ports via standard Windows drivers enable PC applications to run simultaneously Packet Data and AT Commands)		
	USB 2.0 support for PEI (Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT); rapid programming		
	USB On-The-Go (host & slave) capability for intelligent PEI applications		
Rugged Accessory Connector (GCAI)	GCAI - Motorola accessory and ancillary interface for connection of accessories, data terminals and programming		
General Purpose Input/Output	Digital I/O	7 (4 on remote and motorcycle control head, 3 on transceiver)	
	Analog input	4 (1 on remote and motorcycle control head, with 4 levels)	
SECURITY FEATURES			
Air Interface Encryption	Algorithms	TEA1, TEA2, TEA3	
	Security Classes	Class 1 (Clear), Class 2 (SCK), Class 3G	
	Authentication	Infrastructure initiated and made mutual by terminal	
Provisioning	Secure provisioning tool via Key Variable Loader (KVL)		
User Access Control	PIN/PUK code access		
	Service Profile Selection for Radio User Assignment / Radio User Identity (RUA/RUI) Operation	Based on login credentials, a radio user can be limited to only those radio capabilities defined in pre-installed service profiles, selected by the infrastructure	
Data	Packet Data user authentication		
End to End Encryption (E2EE)	Voice E2EE	Enhanced End-to-End Encryption with OTAR supported through	
	Packet Data E2EE	Universal Crypto Module (UCM) and SIM (via integrated card slot) and or	
	Short Data (SDS) E2EE	CrypTr 2 Broadband IP unit.	
E2EE with SIM Card	Internal SIM Card	Slotted into SIM Card slot on the transceiver	
	External SIM Card	Via External SIM Card Reader connected to rear accessory connector on transceivers or to RJ50 Data port on MTM5500 transceiver	
REGULATORY COMPLIANCE			
Radio (RED Article 3.2)	EN 302 561		
EMC (R&TTE Article 3.1.b)	EN 301 489-1		
	EN 301 489-5		
Electrical Safety (R&TTE Article 3.1.a)	EN 60368		
	EN 50385		
	WEEE Directive		
Environmental	EN50155 (IEC 60571 Ed. 3.0)		
Automotive	E-mark, ECE Regulation No.10 for Electrical/Electronic-Subassembly		
Rail Certification EMC	EN50121-3-2 (IEC 62236-3-2 Ed.2.0)		

³ Future software release

For more information, please visit: motorolasolutions.com/MTM5000

Specifications are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2024 Motorola Solutions, Inc. All rights reserved. (01-24)