

# ST7000

## SMALL TETRA RADIO

The ST7000 small TETRA radio combines a small and discreet form, simple user interface and clear audio. With a hybrid internal and external antenna system, the ST7000 fits easily in a pocket. The touch sensitive buttons, integrated Bluetooth® 4.1 wireless technology, reversible USB-C connector for charging, and 3.5mm audio connector make the ST7000 a flexible, modern TETRA radio.



### KEY FEATURES

- Small and discreet design
- Simple and intuitive user interface
- Vibrate alert and haptic feedback for discreet use
- White OLED screen with touch UI for easy navigation
- Loud and clear audio
- 3.5 mm audio connector for maximum accessory compatibility
- Reversible USB-C connector for flexible charging and programming
- Enhanced coverage with 1.8W transmit power
- Durable with IP54 and MIL-STD 810 F/G rating
- Long-life battery with up to 20 hours of use
- Integrated Bluetooth 4.1 wireless technology
- GPS and GLONASS for location services



# ST7000 SPECIFICATIONS



## GENERAL

Dimensions H x W x D	107 x 60 x 19mm
Weight Including Battery and Antenna	173g
Battery	Removable 2300 mAh IMPRES Li-Ion
Battery Performance	Duty Cycle 5/5/90 > 20 Hours (380-430MHz) / > 19 Hours (800MHz)
	Duty Cycle 5/35/60 > 17 Hours
Audio	Speech Loudness at 30cm: 94 Phon
	Audio Output Power at Rated / Max: 0.9 W
	Audio Distortion at Rated: 1.0 %

## RF SPECIFICATIONS

Frequency Bands	380-430 MHz, 800 MHz
Transmitter RF	Power Class 3L (1.8W) & Class 4 (1W)
Receiver Class	A and B
Rx Static Sensitivity (UHF)	UHF: -116dBm (min); -118dBm (typical) 800 MHz: -114dBm (min); -116dBm (typical)
Rx Dynamic Sensitivity	UHF: -107 dBm (min); -109 dBm (typical) 800 MHz: -105 dBm (min); -107 dBm (typical)

## ENVIRONMENTAL SPECIFICATIONS

Operating Temperature °C	-20 to +55
Storage Temperature °C	-30 to +85
Humidity	ETS 300-019-1-7 Class 7.3E, MIL STD 810 F, G
Dust and Water Ingress Protection	IP54
	Dust, Driving Rain Protection
Shock, Drop and Vibration	ETS 300-019 1-7 class 5M3; MIL-STD 810 F/G

## MAIN VOICE SERVICES

Full Duplex TMO Private, PABX, PSTN, Emergency
Half Duplex TMO Private, Group, Emergency
Half Duplex DMO Private, Group, Emergency
Inter-MNI, Gateway, Repeater Compatible
PTT Double Push
Adaptive Audio Control (AGC)

## Emergency Call Management

Tactical Emergency Group Call to ATTACHED Talkgroup
Non-Tactical Emergency Group Call to DEDICATED Talkgroup
HOT MIC Emergency - Hands Free in Moments That Matter
Emergency Status Msg Sent to Dispatch Console
Preemptive Priority Calls

## DMO Repeater and Gateway Services

Works with DMO Repeaters and Gateways <sup>1</sup>
--

## BLUETOOTH AUDIO & DATA SERVICES

Bluetooth Versions Supported	Bluetooth 2.1 +EDR, Bluetooth 4.1, Bluetooth Smart (BTLE)
Bluetooth Security	Bluetooth 2.1 Introduces Mandatory Encryption with Secure Simple Pairing (SSP), Easier Pairing and Preventing Sniffing / Hacking
Bluetooth Audio	HeadSet Profile, Fast PTT with Motorola Solutions Accessories
Bluetooth Data Services	Serial Port Profile, Dial Up Networking Profile, Discovery Mode, Generic Access Profile, Generic Attributes Profile (GATT), Heart Rate Profile, Battery Service Profile, Devices Info Profile.

## LOCATION SERVICES

Constellations Supported	GPS and GLONASS
Simultaneous Satellites	12
Tracking Sensitivity	Integrated Internal Antenna
Accuracy	-163 dBm
Protocols	< 5metre (50% probable) @ -130 dBm
	ETSI LIP, LRRP

<sup>1</sup> Does not work as a DMO repeater.

# ST7000 SPECIFICATIONS

## USER INTERFACE

### Hard Keys

High Tactility PTT

Power / Wakeup Button

Talkgroup Change Rocker Switch

Volume up / down

2 Configurable One Touch Buttons, Extensive List of Functions

### Touch User Interface

Touch sensitive menu icons usable with gloves or in the rain

Simplified user interface

Menu editor, simplify and tailor to user needs

### Display

PMOLED 128 x 64 pixels, white

### Simplified User Interface

Favourite Talkgroups

Favourite Contacts

Bluetooth

Radio Settings

My Info

Language Options

### Advanced User Interface

Talkgroups – TMO Folders: 256, TMO Unique: 10,000

Talkgroups – DMO Folders: 128, DMO Groups: 2,000

Talkgroups – Extended Folders: 330, Mixed TMO/DMO Groups: up to 15 groups per folder

Country/Network Code List - up to 100, by contact or talkgroup

Scan Lists - 40 lists of up to 20 groups

Contacts - up to 1000 with 6 numbers per contact (max 2000 unique numbers)

Fast/Flexible Call Set Up / Answer

Multiple Ring Tones possible

### Text & Status Messaging

SDS Messaging

Call-Out<sup>2</sup>

## SECURITY & SAFETY OPTIONS

Man Down<sup>3</sup> (Fall Alert)

PIN Lock – Personal Identification Number (PIN) and PIN Unblocking Key (PUK)

Enhanced Security - OTAR/DMO SCK

Authentication (Mutual)

Air Interface Encryption (ETSI / SFPG TEA Algorithms)

Security Class 1, 2, 3 and 3G support

End-to-End Encryption: Hardware Security Module (HSM)

BOS Smart Card support

Permanent Disable (ETSI, V2-Customer Restore)

Temporary Disable (Stun)

## DATA & MESSAGING SERVICES

Secondary Control Channel

ETSI and Enhanced AT Commands (including Voice Control and Short Data)

TNP1 - Support simultaneous Packet Data and Short Data Services over PEI

iTM Fleet Management (Remote Programming)

Wi-Fi hardware ready

<sup>2</sup> Licensed Feature

<sup>3</sup> Licensed Feature. Note: ST7000 supports no movement detection only.

## SMALL AND DISCREET

The ST7000 small TETRA radio combines a discreet form, simple user interface and high quality audio.



LED Coverage Indicator

Full Duplex Earpiece

OLED Display

Touch User Interface

Open Speaker Port



3.5mm Audio Jack

USB-C Connector

Microphone



For more information, please visit: [motorolasolutions.com/ST7000](https://motorolasolutions.com/ST7000)

Motorola Solutions UK Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2023 Motorola Solutions, Inc. All rights reserved. (04-23)